# RCK-308MA

3U Rackmount Chassis with (4) 5.25" and (4) 3.5" Drive Bays for ATX Motherboard, with Temperature Monitor Board, Supports ATX PSU



# Introduction

The RCK-308MA 3U Rack mount Chassis provides a classy and resourceful solution for a variety of Industrial applications using ATX motherboard. Besides external four 5.25" bays and two 3.5" bays, RCK-308MA offers two 3.5" shock resistive drive bays; sufficient for applications that use guite significant number of drivers without having to use very bulky 4U chassis. Two levels temperature management relies on one ball bearing 6cm fan that provide excellent cooling and System Environmental Monitor that warns users when the system temperature is above normal. One extra space for optional additional fan is provided for more heat sensitive application. RCK-308MA offers two alternative positions for two 2.0 USB ports.

# **Features**

• Standard 3U 19" Rackmount Chassis


ADVANCED INDUSTRIAL CON

- Heavy Duty Steel with Ni plating RoHS compliant
- Front Panel with Lockable Doors to Protect Drives
- (4) 5.25", (2) 3.5" FDD, (2) 3.5" internal HDD drive bays with shock-resistant drive brackets
- (2) 2.0 USB ports with two alternative positions to choose
- Supports ATX Motherboard
- System Environmental Monitor
- Extra space for one additional 6cm fan



# RCK-308MA

## **Mechanical Drawing**



## Construction

 Zinc-Coated Steel with Aluminum Alloy front bezel

# Color

Black

#### **Board Support**

ATX Motherboard

## **Drive Bays**

• (4) 5.25" and (2) 3.5" external drives and (2) 3.5" internal drives

#### Expansion

7-Slots for full size add-on cards

#### **Power Supply**

• Supports ATX power supply

#### **Cooling System**

6 cm and environmental monitoring board.
One extra space for additional 6cm fan

#### Ports

Two USB ports on front panel

# Switches

On/Off Switch and Reset Switch

#### Indicators

• LED for Power ON/OFF, HDD, Fan & Alarm

ADVANCED INDUSTRIAL COMPUTER SYSTEMS

#### Dimensions

- 427 (W) x 480 (D) x 132.6 (H)mm
- 16.8 (W) x 18.9 (D) x 5.2 (H) inches

## **Operating Temperature**

• 0~55 °C

# **Gross Weight**

• 13.8kg

# **Ordering Information**

RCK-308MA	3U chassis for ATX motherboard with (4)
	5.25", (2) 3.5" FDD, (2) 3.5" Internal
	drive bays
RCK-308MA-300W	RCK-308MA with 300W Power Supply
RCK-308MA-380W	RCK-308MA with 380W Power Supply
MT-SR01	Optional Slide Rail

